

Technical data sheet Version 1

impregnation for floor TY 2316-003-49630959-04

Purpose To increase the service life of wooden surfaces exposed to intensive moisture, high temperature and mechanical stress

Properties Deeply penetrates and protects wood from blue stain, mold, fungus, wood insects. It has dirt and water repellent properties. Does not form a slippery film coating.

Composition Acrylic dispersion
Hydrophobizing additives
Water

Packing Plastic containers of 1 l, 3 l.

Technical Specifications

Appearance	Milk liquid
Frost resistance, cycles	5
Drying time up to degree 3 at (20±2) °C, hour, not more	1 72

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 24 months from the date of manufacture.

Transporting By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste management

Containers and unused remains of impregnation after drying are disposed of as household waste.

Safety

Products are fire and explosion-proof and non-toxic. Use personal hand protection equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the date of publication. Published technical data and instructions are subject to change without notice.