

Technical data sheet Version 1

Protective and decorative impregnation AQUA

ТУ 2316-003-49630959-04

Purpose	•	ve finishing of wood, including side and outside the premises.
Properties	strength and adhesiveness	of wood, does not impair its b. It has bioprotective, water
	repellent properties	
Composition	Water Styrene acrylic latex Special antiseptic additives Transparent pigments	
Colors	Colorless Frosting Pine Cowslip Larch Cherry	Mahogany Teak Walnut Oak Wenge Rosewood
Packing	Plastic containers weighing (0.9kg, 2.5kg, 10kg.

Technical Specifications

Film appearance after drying	Smooth, no visible inclusions
Viscosity according to VZ-246 viscometer, nozzle diameter 4 mm, sec, no less	30
Mass fraction of non-volatile substances, %, no less	12
Film resistance to static action of water at (20+2)°C, h, no less	24
Frost resistance, cycles	5
Drying time up to degree 3	1
at (20±2) oC, hour, not more	24
Total drying time, hour	1,03-1,1

Storage conditions	Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.
Guaranteed shelf life	In unopened container manufacturer 60 months from the date of manufacture.
Transportation	By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.
Waste management	Containers and unused remains of impregnation after drying are disposed of as household waste.
Safety	Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to The published technical data and instructions are subject to change without notice.