

Technical data sheet Version 1

Decorator acrylic paint TU 2316-005-49630959-04

Purpose

Bright / pastel colors For decorative painting of small surfaces (wood, brick, concrete, canvas, stucco, etc.) and tinting of acrylic paints, varnishes without limiting the percentage of input. All paints are highly tintable.

Metallics/perlamours For decorative staining and painting of various surfaces (wood, brick, concrete, canvas, stucco and others), as well as for staining of metal and forged products. When added to acrylic lacquers it can be used as a glaze compound. Do not use for tinting paints!

Properties Used for exterior and interior work.

Composition

Bright/pastel colors

Water
Micronized marble
Acrylic latex
Pigment
Target additives

Metallics/perlamours

Water
Acrylic latex
Pigment
Target additives
Corrosion inhibitor

Colors

Bright/pastel colors

- №101, mimosa
- №102, gold ball
- №105, bright orange
- №106, pomegranate
- №107, ruby
- №108, bright pink
- №109, aubergine
- №110, lilac
- №112, cornflower blue
- №113, lagoon
- №114, bright turquoise
- №115, green garden
- №120, brick-red
- №123, night magic
- №125, beige
- №126, peach

Metallic/ pearl

- №141, sage
 - №142, sea
 - №147, pearly gold
 - №148, silver pearl
 - №149, moon pearl
 - №150, cream pearl
 - №151, pink pearl
 - №152, light blue pearl
 - №153, amethyst
 - №154, bohemian ruby
 - №155, red coral
 - №156, red copper
 - №157, chrysolite
 - №158, malachite
 - №159, lazurite
-

- №127, violet
- №128, white
- №129, red
- №130, ripe cherry
- №131, green
- №132, dark chocolate
- №133, ultramarine
- №134, flax
- №135, sesame
- №136, tansy
- №137, apricot
- №138, fir tree
- №139, clover
- №140, jade
- №160, blue steel
- №171, gold metallic
- №172, silver metallic
- №173, pink metallic
- №174, lilac metallic
- №175, emerald metallic
- №176, blue metallic
- №177, leaf-gold
- №178, antique gold
- №179, copper
- №180, bronze
- №182, dark silver
- №194, galaxy
- №195, atlantic
- For exterior and interior work
- For exterior and interior work

Packaging For metallic colors, 0.25 kg plastic containers
For bright/pastel colors 0.32 kg plastic container

Technical Specifications

Film appearance after drying	Smooth, no visible inclusions
Bruckfield viscosity, cPs, sp. 5, V=20 rpm, 25°C	For metallics/pearles: 3000-6000 For bright/pastel colors: 8000-10000
Mass fraction of non-volatile substances, %, min	15
Film resistance to static influence of water at (20±2)°C, h, no less	24
Frost resistance, cycles	5
pH	6,5-8,5
Temperature of application, °C, not less	+5
Drying time up to degree 3 at a temperature of (20±2) °C, hour, not more	1
Total drying time, hour	24
Consumption (for one coat)	150 g/m ²

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 36 months from the date of manufacture.

Transportation

By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste disposal

Containers and unused paint residue are disposed of as household waste after drying.

Safety

The paint is flame retardant and non-toxic. Wear personal protective equipment for hands. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the date of publication. Published technical data and instructions are subject to change without notice.