

## Technical data sheet Version 1

## Shelf impregnation ТУ 2316-003-49630959-04

**Purpose** To protect the shelf of saunas and baths from moisture and dirt, increase service life in conditions of moisture and high temperatures.

---

**Properties** Prevents the darkening of wood, withstands heat up to 1300 C. Preserves the structure, the natural smell of wood. It is not allowed to tint the composition.

---

**Composition** Natural Softener  
Specialty additives  
Water

---

**Packing** Plastic containers of 0.3 l, 1 l.

---

### Technical Specifications

Appearance	Colorless
Frost resistance, cycles	5
Drying time up to degree 3 at (20±2) oC, hour, not more	1 72
Total drying time, hour	1,15-1,2

**Storage conditions** Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

---

**Guaranteed shelf life** In unopened container manufacturer 60 months from the date of manufacture.

---

**Transporting** By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to

---

dangerous goods. Code of emergency measures is not required.

---

**Waste management**

Containers and unused remains of impregnation after drying are disposed of as household waste.

---

**Safety**

Products are fire and explosion-proof and non-toxic. Use personal hand protection equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

---

All information is correct on the date of publication. Published technical data and instructions are subject to change without notice.