

Technical data sheet
Version 1

Anti-mold impregnation
TU 2386-009-49630959-05

Destination To protect wooden, concrete, brick surfaces against mold, mildew and insects inside living quarters under moderate moisture conditions.

Properties Does not form a film and does not tint the wood. Does not have an unpleasant odor.

Composition Aqueous solution of salts.

Packaging Plastic containers weighing 1kg, 5kg, 10kg.

Technical Specifications

Appearance	Colorless or light straw liquid, slight turbidity and sediment are allowed.
Density at 20°C, g/cm ³	1,03-1,12
Frost resistance, cycles	5
pH	2,5-5,5
Consumption (per coat)	1 liter per 5-7 m ²

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not below 0°C. In case of freezing, thaw products at room temperature and mix thoroughly until homogeneous mass. After thawing it retains its full properties.

Guaranteed shelf life In unopened container manufacturer 60 months from the date of manufacture.

Transportation By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste management The remains of the composition are mixed with sawdust and dried in domestic conditions. Container and dried composition

are disposed as household waste.

Security

Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil. Do not use on metal, painted, glass surfaces and tiles.

All information is correct on the day of publication. Published technical data and instructions may be changed without prior notice.